

Printing date 03/01/2019

Reviewed on 03/01/2019

Page 1/11

1 Identification

- · Product identifier
- · Trade name: CEC02.1 G-Max Euro Clear 2:1:1
- · Article number: CEC02.1
- · Details of the supplier of the safety data sheet

• *Manufacturer/Supplier:* Lusid Technologies 5195 West 4700 South KEARNS, UT 84118 USA www.lusid.biz

 Information department: Product safety department
 Emergency telephone number: 24 Hrs Emergency Contact:

INFOTRAC 1-800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture

GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



(Contd. on page 2)

Printing date 03/01/2019

Reviewed on 03/01/2019

Trade name: CEC02.1 G-Max Euro Clear

· Signal word [Contd. of page 1)
-	nining components of labeling:
n-butyl acetate	
acetone	
	entamethyl-4-piperidyl)sebacate
· Hazard stater	
Highly flamma	ble liquid and vapor.
Causes skin ir	
Causes seriou	s eye irritation.
May cause an	allergic skin reaction.
	wsiness or dizziness.
Precautionary	r statements
	m heat/sparks/open flames/hot surfaces No smoking.
	container and receiving equipment.
	proof electrical/ventilating/lighting/equipment.
Use only non-	
	nary measures against static discharge.
	g dust/fume/gas/mist/vapors/spray
	hly after handling.
	pors or in a well-ventilated area.
	work clothing must not be allowed out of the workplace.
	e gloves/protective clothing/eye protection/face protection.
	air): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	Remove person to fresh air and keep comfortable for breathing.
	se cautiously with water for several minutes. Remove contact lenses, if present and easy
to do. Continue	ennsing. enter/doctor if you feel unwell.
	ent (see on this label).
	minated clothing and wash it before reuse.
	or rash occurs: Get medical advice/attention.
	persists: Get medical advice/attention.
	nated clothing before reuse.
	Use for extinction: CO2, powder or water spray.
	ventilated place. Keep container tightly closed.
	ventilated place. Keep cool.
Store locked u	
	tents/container in accordance with local/regional/national/international regulations.
Classification	
NFPA ratings	
F	lealth = 2
	ire = 3
	Peactivity = 0
HMIS-ratings	(scale 0 - 4)
_	
	Health = 2
	Fire = 3
REACTIVITY 0	Reactivity = 0
Other hazard	3
	, T and vPvB assessment
PBT: Not appl	
	(Contd. on page 3)

(Contd. on page 3)

- USA

(Contd. of page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/01/2019

Reviewed on 03/01/2019

Trade name: CEC02.1 G-Max Euro Clear

· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

Dungeroue	componente.	
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	10-25%
123-86-4	n-butyl acetate	10-25%
67-64-1	acetone	2.5-10%
110-43-0	heptan-2-one	≤2.5%
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	≤2.5%

4 First-aid measures

· Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • For safety reasons unsuitable extinguishing agents: Water with full jet

- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 4)

Printing date 03/01/2019

Reviewed on 03/01/2019

Trade name: CEC02.1 G-Max Euro Clear

		(Contd. of page 3
	to other sections n 7 for information on safe handling.	
	n 8 for information on personal protection equipment.	
	n 13 for disposal information. Action Criteria for Chemicals	
Protective PAC-1:	Action Criteria for Chemicais	
-	n-butyl acetate	5 ppm
	acetone	200 ppm
110-43-0	heptan-2-one	150 ppm
1330-20-7		130 ppm
122-99-6	2-Phenoxyethanol	1.5 ppm
100-41-4	ethylbenzene	33 ppm
77-58-7	dibutyltin dilaurate	1.1 mg/m ³
108-88-3	toluene	67 ppm
PAC-2:		
123-86-4	n-butyl acetate	200 ppm
67-64-1	acetone	3200* ppm
110-43-0	heptan-2-one	670 ppm
1330-20-7	xylene	920* ppm
122-99-6	2-Phenoxyethanol	16 ppm
100-41-4	ethylbenzene	1100* ppm
77-58-7	dibutyltin dilaurate	8 mg/m³
108-88-3	toluene	560 ppm
PAC-3:		
123-86-4	n-butyl acetate	3000* ppm
67-64-1	acetone	5700* ppr
110-43-0	heptan-2-one	4000* ppm
1330-20-7	xylene	2500* ppm
122-99-6	2-Phenoxyethanol	97 ppm
100-41-4	ethylbenzene	1800* ppm
77-58-7	dibutyltin dilaurate	48 mg/m³
108-88-3	toluene	3700* ppm

7 Handling and storage

- · Handling:
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.

(Contd. on page 5)

⁻ USA

Printing date 03/01/2019

Reviewed on 03/01/2019

Trade name: CEC02.1 G-Max Euro Clear

(Contd. of page 4)

· Further info	ormation about storage conditions:	
Keep recept	acle tightly sealed.	
Otoria in ana	I day a politicano in wall cooled accorded	1

Store in cool, dry conditions in well sealed receptacles.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m³, 150 ppm

- REL Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm
- TLV Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm

67-64-1 acetone

- PEL Long-term value: 2400 mg/m³, 1000 ppm
- REL Long-term value: 590 mg/m³, 250 ppm
- TLV Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm BEI

110-43-0 heptan-2-one

PEL Long-term value: 465 mg/m³, 100 ppm

REL Long-term value: 465 mg/m³, 100 ppm

TLV Long-term value: 233 mg/m³, 50 ppm

· Ingredients with biological limit values:

67-64-1 acetone

BEI 50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.
- Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 6)

USA

Printing date 03/01/2019

Reviewed on 03/01/2019

Trade name: CEC02.1 G-Max Euro Clear

(Contd. of page 5)

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

 Information on basic physical and General Information 	enemiea properties
Appearance:	Linuid
Form:	Liquid Clear
Color: · Odor:	Chear Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined (pH N/A in solvent coatings)
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. 55 °C (131 °F)
· Flash point:	-17 °C (1.4 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	370 °C (698 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %

USA

Printing date 03/01/2019

Reviewed on 03/01/2019

Trade name: CEC02.1 G-Max Euro Clear

		(Contd. of page 6
Upper:	13 Vol %	
· Vapor pressure at 20 °C (68 °F):	233 hPa (174.8 mm Hg)	
· Density at 20 °C (68 °F):	1.0574 g/cm³ (8.824 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wat	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	29.5 %	
VOC content:	19.73 %	
	208.7 g/l / 1.74 lb/gal	
Solids content:	47.3 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided:
 No decomposition if used opporting to apositions
- No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:
- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1330-20-7 xylene

100-41-4 ethylbenzene

(Contd. on page 8)

USA

3

(Contd. of page 7)

3

Safety Data Sheet acc. to OSHA HCS

Printing date 03/01/2019

Reviewed on 03/01/2019

Trade name: CEC02.1 G-Max Euro Clear

108-88-3 toluene

· NTP (National Toxicology Program)

None of the ingredients is listed.

• OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.

UN-Number		
DOT, IMDG, IATA	UN1263	
UN proper shipping name		
DOT	Paint	
IMDG, IATA	PAINT	
Transport hazard class(es)		
DOT, IMDG, IATA		
Class	3 Flammable liquids	

Printing date 03/01/2019

Reviewed on 03/01/2019

Trade name: CEC02.1 G-Max Euro Clear

	(Contd. of pag
Label	3
· Packing group · DOT, IMDG, IATA	11
· Environmental hazards: · Marine pollutant:	No
 Special precautions for user Danger code (Kemler): EMS Number: Stowage Category 	Warning: Flammable liquids 33 F-E, <u>S-E</u> B
 Transport in bulk according to Annex MARPOL73/78 and the IBC Code 	<i>II of</i> Not applicable.
 Transport/Additional information: DOT Quantity limitations 	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

	55 (extremely hazardous substances): e ingredients is listed.	
	13 (Specific toxic chemical listings):	
1330-20-7		
	2-Phenoxyethanol	
100-41-4	ethylbenzene	
108-88-3	toluene	
TSCA (Tox	kic Substances Control Act):	
All ingredie	nts are listed.	
Propositio	on 65	
Chemicals	s known to cause cancer:	
100-41-4 e	ethylbenzene	
Chemicals	s known to cause reproductive toxicity for females:	
None of the	e ingredients is listed.	
Chemicals	s known to cause reproductive toxicity for males:	
Vone of the	e ingredients is listed.	
		(Contd. on pag

Printing date 03/01/2019

Reviewed on 03/01/2019

Trade name: CEC02.1 G-Max Euro Clear

		(Contd. of page
Chemical	s known to cause developmental toxicity:	
108-88-3	toluene	
Carcinoge	enic categories	
EPA (Env	ironmental Protection Agency)	
67-64-1	acetone	
1330-20-7	xylene	1
100-41-4	ethylbenzene	L
108-88-3	toluene	
TLV (Thre	shold Limit Value established by ACGIH)	
67-64-1	acetone	A
1330-20-7	xylene	A
100-41-4	ethylbenzene	A
77-58-7	dibutyltin dilaurate	A
108-88-3	toluene	A

None of the ingredients is listed.

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling: *n-butyl* acetate acetone bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. (Contd. on page 11)

on page 11)

Printing date 03/01/2019

Reviewed on 03/01/2019

Trade name: CEC02.1 G-Max Euro Clear

(Contd. of page 10)

USA

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Wash contaminated clothing before reuse. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Product Safety Dept.
- · Date of preparation / last revision 03/01/2019 / 8
- · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 2: Flammable liquids - Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 • * Data compared to the previous version altered.